

BR67 HYDRAULIC BREAKER

STANLEY®



Stanley's line of handheld breakers contains a wide selection of models suited to virtually any application.

The BR67 is a medium duty tool for work in the 70 - 90 pound class. It is highly productive in utility construction, street maintenance, repair of water and gas mains, and general contracting jobs.

Available in both a T-Handle and Anti-Vibration Handle model.

Spring dampened, anti-vibration handles (BR67125 and BR67135) reduces operator fatigue, allowing the breaker to float in the user's hands. Built in handle stops allow the operator to apply full body weight in tough applications.

Easi-Ride™ foot, offered on the BR67 absorbs and controls tool bit bounce, greatly reducing operator fatigue.

Feathering on/off valve controls blow speed, making startup and initial tool placement easy.

Diaphragm accumulator provides trouble free operation with system back pressures up to 250 psi (17 bar). Accumulator on BR67125 and BR67135 can be serviced without disassembling the tool. Both models operate on open center systems and are available in 1-1/8 or 1-1/4 in. hex sizes.

Complete line of steels for breaking, cutting or driving available from Stanley Hydraulic Tools.

Underwater models available.

SPECIFICATIONS

| ITEM | | |
|---------------------|---|---------------|
| Output | 0 - 1300 Blows Per Minute Range | |
| Input Flow Range | 7 - 9 gpm | 26 - 34 lpm |
| Input Pressure | 1500 - 2000 psi | 105 - 140 bar |
| Max. Back Pressure | 250 psi | 17 bar |
| Optimum Flow | 8 gpm | 30 lpm |
| Porting | -8 SAE O-Ring | |
| Connector | 3/8 in. Male Pipe Hose End | |
| BR67 | | |
| Steel Capacity | 6 x 1-1/4 in. Hex and 6 x 1-1/8 in. Hex | |
| Weight | 67 / 72 lb | 30 / 33 kg |
| Length | 27 in. | 68 cm |
| Width (At Handles) | 16 in. | 41 cm |
| BR67125 and BR67135 | | |
| Steel Capacity | 6 x 1-1/8 in. Hex and 6 x 1-1/4 in. Hex | |
| Weight | 78 lb | 36 kg |
| Length | 29 in. | 73 cm |
| Width (At Handles) | 18 in. | 46 cm |



BR67 HYDRAULIC BREAKER

STANLEY®

| Model Numbers | |
|---------------|---|
| Model | Description |
| BR67120 | BR67 T-Handle Breaker, 1-1/8 in. Hex |
| BR67120E | BR67 T-Handle Breaker, 1-1/8 in. Hex, Easi-Ride™ Foot |
| BR67130 | BR67 T-Handle Breaker, 1-1/4 in. Hex |
| BR67130E | BR67 T-Handle Breaker, 1-1/4 in. Hex, Easi-Ride™ Foot |
| BR67320 | BR67 Underwater T-Handle Breaker, 1-1/8 in. Hex, CE |
| BR67125 | BR67S Anti-Vibration Handle Breaker, 1-1/8 in. Hex |
| BR67135 | BR67S Anti-Vibration Handle Breaker, 1-1/4 in. Hex |

| Service Tools | |
|----------------|---------------------------------|
| Part No. | Description |
| 04596 | Seal Kit |
| 04908 | Split Ring (Auto Valve Removal) |
| 04909 | Spacer (Flow Sleeve Install) |
| 04910 | Flow Sleeve Removal Tube |
| 05508 | Accumulator Disassembly Tool |
| 05640 | Accumulator Cylinder Puller |
| Test Equipment | |
| 02835 | Accumulator Tester |
| 04182 | Flow and Pressure Tester |
| 31254 | Accumulator Charge Kit |

Note: All models listed above ship with hose whips.

| Part | Description |
|-----------------------------------|---|
| 1-1/8 in Hex X 6 in. Shank | |
| 02331 | Clay Spade, 5-1/2 In. / 14 cm Blade |
| 02332 | Asphalt Cutter, 5 in. / 12.7 cm Blade x 11 in. / 28 cm* |
| 02333 | Moil Point, 14 in. / 25.6 cm* |
| 02334 | Chisel, 3 in. / 76 mm Blade x 14 in. / 35.6 cm* |
| 03990 | Chisel Point, 14 in. / 35.6 cm* |
| 04176 | Ground Rod Driver, 1 in. / 25 mm Rod |
| 08106 | Asphalt Wedge, 12 in. / 30.5 cm* |

| Part | Description |
|-----------------------------------|--|
| 1-1/4 in Hex X 6 in. Shank | |
| 02335 | Asphalt Cutter, 5 In. / 12.7 Cm Blade x11 In. / 28 cm* |
| 02336 | Moil Point, 14 in. / 35.6 cm* |
| 02337 | Chisel, 3 in. / 76 mm Blade x 14 in. / 35.6 cm* |
| 02338 | Heavy Duty Chisel, 1 in. / 25 mm x 14 in. / 35.6 cm* |
| 04367 | Ground Rod Driver, 1 in. / 25 mm Rod |
| 04404 | Heavy Duty Moil Point, 18 in. / 45.7 cm* |
| 04405 | Clay Spade, 8 in. / 20.3 cm Blade |
| 08119 | Asphalt Wedge |
| 09262 | Clay Spade, 5-1/2 in. / 14 cm |
| 17782 | Detachable Shank |

All stanley hydraulic tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your application, please consult stanley hydraulic tools.

WARRANTY:

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.